

**Safety Data Sheet
NUMIX FADE OUT THINNER**

SECTION 1: Identification**1.1 Product identifier**

Product name NUMIX FADE OUT THINNER

1.2 Supplier's details

Name National Paints Factories Co. Limited
Address Maliha Road Industrial Area 13
Sharjah
5822 Sharjah Sharjah
United Arab Emirates

Telephone +971 6 5130000
Fax +971 6 5340222
email npfcl@nationalpaints.com

1.3 Emergency phone number(s)

+971 6 5130000

SECTION 2: Hazard identification**2.1 Classification of the substance or mixture****GHS classification in accordance with: OSHA (29 CFR 1910.1200)**

- Flammable liquids, Cat. 3
- Toxic to reproduction, Cat. 2
- Specific target organ toxicity (single exposure), Cat. 3
- Acute toxicity, inhalation, Cat. 4

2.2 GHS label elements, including precautionary statements**Pictogram****Hazard statement(s)**

H226	Flammable liquid and vapor
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child [effect, route]
H332	Harmful if inhaled

Safety Data Sheet

NUMIX FADE OUT THINNER

Precautionary statement(s)

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER/doctor if you feel unwell.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

SECTION 3: Composition/information on ingredients

3.1 Mixtures

Hazardous components

1. N-Butyl acetate

Concentration	70 - 80 % (weight)
EC no.	204-658-1
CAS no.	123-86-4
Index no.	607-025-00-1
- Flammable liquids, Cat. 3	
- Specific target organ toxicity (single exposure), Cat. 3	
H226	Flammable liquid and vapor
H336	May cause drowsiness or dizziness

2. 2-Ethoxyethyl acetate

Concentration	20 - 30 % (weight)
EC no.	203-839-2
CAS no.	111-15-9
Index no.	607-037-00-7
- Flammable liquids, Cat. 3	
- Toxic to reproduction, Cat. 1B	
- Acute toxicity, inhalation, Cat. 4	
- Acute toxicity, dermal, Cat. 4	
- Acute toxicity, oral, Cat. 4	
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H312	Harmful in contact with skin
H332	Harmful if inhaled

SECTION 4: First-aid measures

Safety Data Sheet

NUMIX FADE OUT THINNER

4.1 Description of necessary first-aid measures

General advice	Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
If inhaled	If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.
In case of skin contact	Rinse with plenty of water. Get medical attention if irritation develops and persists.
In case of eye contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
If swallowed	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms/effects, acute and delayed

The most important known symptoms and effects are described in the labeling (see section 2.2) and/or in section 11

4.3 Indication of immediate medical attention and special treatment needed, if necessary

No data available

SECTION 5: Fire-fighting measures

5.1 Suitable extinguishing media

Use extinguishing media appropriate for surrounding fire.

5.2 Specific hazards arising from the chemical

No further relevant information available.

5.3 Special protective actions for fire-fighters

Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

Safety Data Sheet

NUMIX FADE OUT THINNER

7.1 Precautions for safe handling

Avoid inhalation of vapour or mist. Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build-up of electrostatic charge. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

1. N-Butyl acetate (CAS: 123-86-4 EC: 204-658-1)

PEL (Inhalation): 150 ppm (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 710 mg/m³ (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 150 ppm, (ST) 200 ppm (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): 150 ppm, (ST) 200 ppm (NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

TLV® (Inhalation): 150 ppm, (ST) 200 ppm; USA (ACGIH)

OSHA Annotated Table Z-1, www.osha.gov

STEL (Inhalation): 200 ppm

950 mg/m³ (Cal/OSHA)

California permissible exposure limits for chemical contaminants
(Title 8, Article 107)

PEL (Inhalation): 150 ppm

710 mg/m³

California permissible exposure limits for chemical contaminants
(Title 8, Article 107)

2. 2-Ethoxyethyl acetate (CAS: 111-15-9)

PEL (Inhalation): 100 ppm (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 540 mg/m³ (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 5 ppm (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): 0.5 ppm (NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

8.2 Individual protection measures, such as personal protective equipment (PPE)

Body protection

Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Safety Data Sheet

NUMIX FADE OUT THINNER

Respiratory protection is not required. Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN 143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Thermal hazards

No data available

Environmental exposure controls

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance/form (physical state, color, etc.)	Liquid
Odor	Characteristic
Odor threshold	Not determined.
pH	Not determined.
Melting point/freezing point	Undetermined.
Initial boiling point and boiling range	124 °C
Flash point	31 °C
Evaporation rate	Not determined.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability limits	Not determined.
Upper/lower explosive limits	Not determined.
Vapor pressure	10.7 hPa @ 20 °C
Vapor density	Not determined.
Relative density	Not determined.
Solubility(ies)	Not miscible or difficult to mix with water.
Partition coefficient: n-octanol/water	Not determined.
Auto-ignition temperature	Not determined.
Decomposition temperature	Not determined.
Viscosity	Not determined.
Explosive properties	Not determined.
Oxidizing properties	Not determined.

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

No data available

10.3 Possibility of hazardous reactions

None under normal use conditions.

10.4 Conditions to avoid

Avoid storing in direct sunlight and avoid extremes of temperature.

10.5 Incompatible materials

N-Butyl acetate: Strong oxidizing agents, Strong reducing agents, Strong bases

10.6 Hazardous decomposition products

N-Butyl acetate: Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

SECTION 11: Toxicological information

Safety Data Sheet

NUMIX FADE OUT THINNER

Information on toxicological effects

Acute toxicity

2-Ethoxyethyl acetate

LD50 Inhalation - Rat - 4 h

N-BUTYLACETATE

LC50 Inhalation - Rat - 21 mg/l - 4 h

Citation: (OECD Test Guideline 403)

Skin corrosion/irritation

Irritating to skin.

Serious eye damage/irritation

Causes eye irritation.

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

Reproductive toxicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration hazard

No data available

Additional information

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: Ecological information

Toxicity

No data available on product

Persistence and degradability

No data available on product

Bioaccumulative potential

No data available on product

Mobility in soil

No data available

Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects

Safety Data Sheet

NUMIX FADE OUT THINNER

No data available

SECTION 13: Disposal considerations

Disposal of the product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

Disposal of contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

DOT (US)

UN Number: UN1263

Class: 3 Flammable liquids.

Packing Group: III

Proper Shipping Name: 1263 PAINT

Reportable quantity (RQ):

Marine pollutant:

Poison inhalation hazard:

IMDG

UN Number: UN1263

Class: 3 Flammable liquids.

Packing Group: III

EMS Number: F-E,S-E

Proper Shipping Name: 1263 PAINT

IATA

UN Number: UN1263

Class: 3 Flammable liquids.

Packing Group: III

Proper Shipping Name: 1263 PAINT

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

Massachusetts Right To Know Components

n-Butyl acetate

CAS number: 123-86-4

New Jersey Right To Know Components

n-Butyl acetate

CAS number: 123-86-4

Pennsylvania Right To Know Components

n-Butyl acetate

CAS number: 123-86-4

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

Safety Data Sheet

NUMIX FADE OUT THINNER

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SARA 311/312 Hazards

Fire Hazard

New Jersey Right To Know Components

Common name: 2-ETHOXYETHYL ACETATE

CAS number: 111-15-9

Pennsylvania Right To Know Components

Chemical name: Ethanol, 2-ethoxy-, acetate

CAS number: 111-15-9

California Prop. 65 components

Chemical name: 2-Ethoxyethyl acetate

CAS number: 111-15-9

01/01/1993 - Developmental toxicity

01/01/1993 - Male reproductive toxicity

SECTION 16: Other information

16.1 Further information/disclaimer

DISCLAIMER: The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of information for their particular purposes. In no event shall National Paints Factories Co. Ltd be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, whatsoever arising, even if National Paints Factories Co. Ltd has been advised of the possibility of such damages.