

**Safety Data Sheet
NUMIX POLYESTER PUTTY SOFT**

SECTION 1: Identification

1.1 Product identifier

Product name	NUMIX POLYESTER PUTTY SOFT
Brand	NUMIX

1.2 Supplier's details

Name	National Paints Factories Co. Limited
Address	Maliha Road Industrial Area 13 Sharjah 5822 Sharjah Sharjah United Arab Emirates
Telephone	+971 6 5130000
Fax	+971 6 5340222
email	npfcl@nationalpaints.com

1.3 Emergency phone number(s)

+971 6 5130000

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

GHS classification in accordance with: OSHA (29 CFR 1910.1200)

- Flammable liquids, Cat. 3
- Carcinogenicity, Cat. 2
- Toxic to reproduction, Cat. 2
- Specific target organ toxicity (repeated exposure), Cat. 1
- Skin corrosion/irritation, Cat. 2
- Eye damage/irritation, Cat. 2A

2.2 GHS label elements, including precautionary statements

Pictogram



Safety Data Sheet

NUMIX POLYESTER PUTTY SOFT

Hazard statement(s)

H226	Flammable liquid and vapor
H315	Causes skin irritation
H319	Causes serious eye irritation
H351	Suspected of causing cancer [route]
H361	Suspected of damaging fertility or the unborn child [effect, route]
H372	Causes damage to organs [organs] through prolonged or repeated exposure [route]

Precautionary statement(s)

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

SECTION 3: Composition/information on ingredients

3.1 Mixtures

Hazardous components

1. STYRENE

Concentration	5 - 15 % (weight)
EC no.	202-851-5
CAS no.	100-42-5
Index no.	601-026-00-0

- Flammable liquids, Cat. 3
- Toxic to reproduction, Cat. 2
- Acute toxicity, inhalation, Cat. 4
- Specific target organ toxicity (repeated exposure), Cat. 1
- Skin corrosion/irritation, Cat. 2
- Serious eye damage/eye irritation, Cat. 2

H226	Flammable liquid and vapor
H315	Causes skin irritation

Safety Data Sheet

NUMIX POLYESTER PUTTY SOFT

H319	Causes serious eye irritation
H332	Harmful if inhaled
H361d	
H372	Causes damage to organs [organs] through prolonged or repeated exposure [route]

2. Fatty acids, castor-oil, caustic-oxidized, distn residues, esters with 1,3-butanediol

Concentration	15 - 25 % (weight)
CAS no.	113669-95-7

- Flammable liquids, Cat. 3
- Toxic to reproduction, Cat. 2
- Acute toxicity, inhalation, Cat. 4
- Specific target organ toxicity (repeated exposure), Cat. 1
- Skin corrosion/irritation, Cat. 2
- Serious eye damage/eye irritation, Cat. 2

H226	Flammable liquid and vapor
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H361d	
H372	Causes damage to organs [organs] through prolonged or repeated exposure [route]

SECTION 4: First-aid measures

4.1 Description of necessary first-aid measures

General advice	In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).
If inhaled	Call a poison center or doctor if you feel unwell. Acute and delayed symptoms and effects: May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.
In case of skin contact	Wash with plenty of soap and water for at least 15 minutes. Call a poison center or doctor if you feel unwell. Acute and delayed symptoms and effects: May cause skin irritation. Signs/symptoms may include localized redness, swelling, and itching.
In case of eye contact	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor. Acute and delayed symptoms and effects: May cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.
If swallowed	Rinse mouth. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Call a poison center or doctor if you feel unwell.

Safety Data Sheet

NUMIX POLYESTER PUTTY SOFT

4.2 Most important symptoms/effects, acute and delayed

The most important known symptoms and effects are described in the labeling (see section 2) and/or in section 11.

4.3 Indication of immediate medical attention and special treatment needed, if necessary

No further relevant information available.

SECTION 5: Fire-fighting measures

5.1 Suitable extinguishing media

CO₂, sand, extinguishing powder.

5.2 Specific hazards arising from the chemical

During heating or in case of fire poisonous gases are produced.

5.3 Special protective actions for fire-fighters

Wear self-contained breathing apparatus for firefighting if necessary.

Further information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Use personal protection recommended in Section 8.

As an immediate precautionary measure, isolate spill or leak area in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate enclosed areas.

6.2 Environmental precautions

Keep out of drains, sewers, ditches, and waterways.

6.3 Methods and materials for containment and cleaning up

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.

Reference to other sections

For disposal see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed. Keep out of the reach of children.

Specific end use(s)

Apart from the uses mentioned in section 1 no other specific uses are stipulated.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

1. Styrene (CAS: 100-42-5)

PEL (Inhalation): See Annotated Z-2 ppm (OSHA)

Safety Data Sheet

NUMIX POLYESTER PUTTY SOFT

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): See Annotated Z-2 mg/m³ (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): See Annotated Z-2 (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): See Annotated Z-2 (NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

8.2 Appropriate engineering controls

If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

8.3 Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Safety glasses with side-shields.

Skin protection

Protective gloves, such as nitrile gloves

Body protection

Wear protective clothing. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Thermal hazards

No data available

Environmental exposure controls

Do not let product enter drains. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance/form (physical state, color, etc.)	Paste/Putty
Odor	Not determined
Odor threshold	No data available.
pH	Not determined
Melting point/freezing point	No data available.
Initial boiling point and boiling range	No data available.
Flash point	31°C(87.8°F)
Evaporation rate	No data available.
Flammability (solid, gas)	No data available.
Upper/lower flammability limits	No data available.
Upper/lower explosive limits	No data available.
Vapor pressure	No data available.

Safety Data Sheet

NUMIX POLYESTER PUTTY SOFT

Vapor density	
Relative density	1.82
Solubility(ies)	No data available.
Partition coefficient: n-octanol/water	No data available.
Auto-ignition temperature	No data available.
Decomposition temperature	Product is not self-igniting
Viscosity	No data available.
Explosive properties	No data available.
Oxidizing properties	No data available.

Other safety information

Wt. % Solids: 85.5

Wt. % Volatiles: 14.5%

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

Stable under normal conditions

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

Contact with incompatible materials. Sources of ignition. Exposure to heat.

10.5 Incompatible materials

Strong acids and Oxidizing agents

10.6 Hazardous decomposition products

No data available.

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Likely Routes of Exposure: Eye contact. Skin contact. Inhalation. Ingestion.

Symptoms (including delayed and immediate effects):

Inhalation: May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Ingestion: May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Skin corrosion/irritation

May cause skin irritation. Signs/symptoms may include localized redness, swelling, and itching.

Serious eye damage/irritation

May cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Respiratory or skin sensitization

No data available.

Germ cell mutagenicity

No data available.

Safety Data Sheet

NUMIX POLYESTER PUTTY SOFT

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification IARC: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

No data available.

Summary of evaluation of the CMR properties

No data available.

STOT-single exposure

No data available.

STOT-repeated exposure

No data available.

Aspiration hazard

No data available.

Additional information

No data available.

SECTION 12: Ecological information

Toxicity

No data available on product.

Persistence and degradability

No data available on product.

Bioaccumulative potential

No data available on product.

Mobility in soil

No data available on product.

Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted.

Other adverse effects

No data available on product.

SECTION 13: Disposal considerations

Disposal of the product

Disposal should be in accordance with applicable Federal, State and local laws and regulations. Local regulations may be more stringent than State or Federal requirements.

Disposal of contaminated packaging

Dispose of as unused product.

Safety Data Sheet

NUMIX POLYESTER PUTTY SOFT

Waste treatment

Must not be disposed together with household garbage Do not allow product to reach sewage system.

SECTION 14: Transport information

DOT (US)

UN Number: UN3269

Class: 3 Flammable liquids

Packing Group: III

Proper Shipping Name: POLYESTER RESIN KIT

Reportable quantity (RQ):

Marine pollutant:

Poison inhalation hazard:

IMDG

UN Number: UN3269

Class: 3 Flammable liquids

Packing Group: III

EMS Number: F-E,S-E

Proper Shipping Name: POLYESTER RESIN KIT

IATA

UN Number: UN3269

Class: 3 Flammable liquids

Packing Group: III

Proper Shipping Name: POLYESTER RESIN KIT

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

Massachusetts Right To Know Components

Chemical name: Styrene

CAS number: 100-42-5

New Jersey Right To Know Components

Common name: STYRENE MONOMER

CAS number: 100-42-5

Pennsylvania Right To Know Components

Chemical name: Benzene, ethenyl-

CAS number: 100-42-5

California Prop. 65 components

Chemical name: STYRENE

CAS number: 100-42-5

22/04/2016 - Cancer


HMIS Rating

NUMIX POLYESTER PUTTY	
HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0
PERSONAL PROTECTION	F

Safety Data Sheet

NUMIX POLYESTER PUTTY SOFT

NFPA Rating



SECTION 16: Other information

16.1 Further information/disclaimer

DISCLAIMER: The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of information for their particular purposes. In no event shall National Paints be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, whatsoever arising, even if National Paints has been advised of the possibility of such damages.