



NATIONAL PAINTS FACTORIES CO. LIMITED

Safety Data Sheet NUMIX WASH PRIMER

SECTION 1: Identification

1.1 Product identifier

Product name	NUMIX WASH PRIMER
Brand	NUMIX

1.2 Other means of identification

No further relevant information available.

1.3 Recommended use of the chemical and restrictions on use

No further relevant information available.

1.4 Supplier's details

Name	National Paints Factories Co. Limited
Address	Maliha Road Industrial Area 13 Sharjah 5822 Sharjah Sharjah United Arab Emirates
Telephone	+971 6 5130000
Fax	+971 6 5340222
email	npfcl@nationalpaints.com

1.5 Emergency phone number(s)

+971 6 5130000

SECTION 2: Hazard identification

General hazard statement

Highly flammable liquid and vapour.
May be harmful in contact with skin.
May be harmful if inhaled.
Causes skin irritation.
Causes serious eye damage.
Harmful to aquatic life.

2.1 Classification of the substance or mixture

GHS classification in accordance with: OSHA (29 CFR 1910.1200)

- Flammable liquids, Cat. 2

Safety Data Sheet

NUMIX WASH PRIMER

- Toxic to reproduction, Cat. 1B
- Eye damage/irritation, Cat. 1
- Skin corrosion/irritation, Cat. 2
- Acute toxicity, inhalation, Cat. 4
- Substances and mixtures which, in contact with water, emit flammable gases, Cat. 3

2.2 GHS label elements, including precautionary statements

Pictogram



Hazard statement(s)

H225	Highly flammable liquid and vapor
H261	In contact with water releases flammable gas
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H332	Harmful if inhaled
H360	May damage fertility or the unborn child [effect, route]

Precautionary statement(s)

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P231+P232	Handle under inert gas. Protect from moisture
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention. Immediately call a POISON CENTER/doctor.
P310	Call a POISON CENTER/doctor if you feel unwell.
P312	Call a POISON CENTER/doctor if you feel unwell.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P363	Wash contaminated clothing before reuse.
P402+P404	Store in a dry place. Store in a closed container.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Safety Data Sheet

NUMIX WASH PRIMER

2.3 Other hazards which do not result in classification

No further relevant information available.

Statement regarding ingredients of unknown toxicity

No further relevant information available.

SECTION 3: Composition/information on ingredients

3.1 Mixtures

Hazardous components

1. sec-Butyl acetate

Concentration	10 - 15 % (weight)
EC no.	203-300-1
CAS no.	105-46-4
Index no.	607-026-00-7

- Flammable liquids, Cat. 2

H225	Highly flammable liquid and vapor
------	-----------------------------------

2. n-Butyl alcohol

Concentration	10 - 15 % (weight)
EC no.	200-751-6
CAS no.	71-36-3
Index no.	603-004-00-6

- Flammable liquids, Cat. 3
- Acute toxicity, oral, Cat. 4
- Specific target organ toxicity (single exposure), Cat. 3
- Skin corrosion/irritation, Cat. 2
- Eye damage/irritation, Cat. 1

H226	Flammable liquid and vapor
H302	Harmful if swallowed
H315	Causes skin irritation
H318	Causes serious eye damage
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness

3. XYLENES (MIXED)

Concentration	10 - 15 % (weight)
EC no.	215-535-7
CAS no.	1330-20-7
Index no.	601-022-00-9

- Flammable liquids, Cat. 3
- Acute toxicity, inhalation, Cat. 4
- Acute toxicity, dermal, Cat. 4
- Skin corrosion/irritation, Cat. 2

H226	Flammable liquid and vapor
H312	Harmful in contact with skin
H315	Causes skin irritation

Safety Data Sheet

NUMIX WASH PRIMER

H332

Harmful if inhaled

4. 2-Butoxyethanol

Concentration	10 - 15 % (weight)
EC no.	203-905-0
CAS no.	111-76-2
Index no.	603-014-00-0

- Skin corrosion/irritation, Cat. 2
- Serious eye damage/eye irritation, Cat. 2
- Acute toxicity, dermal, Cat. 4
- Acute toxicity, inhalation, Cat. 4
- Acute toxicity, oral, Cat. 4

H302

Harmful if swallowed

H312

Harmful in contact with skin

H315

Causes skin irritation

H319

Causes serious eye irritation

H332

Harmful if inhaled

5. 1-Propanol

Concentration	5 - 10 % (weight)
EC no.	200-746-9
CAS no.	71-23-8
Index no.	603-003-00-0

- Flammable liquids, Cat. 2
- Specific target organ toxicity (single exposure), Cat. 3
- Eye damage/irritation, Cat. 1

H225

Highly flammable liquid and vapor

H318

Causes serious eye damage

H336

May cause drowsiness or dizziness

6. Pentazinc chromate octahydroxide

Concentration	5 % (weight)
EC no.	256-418-0
CAS no.	49663-84-5

7. Titanium(IV) oxide

Concentration	5 % (weight)
EC no.	236-675-5
CAS no.	13463-67-7

8. Toluene

Concentration	5 % (weight)
EC no.	203-625-9
CAS no.	108-88-3
Index no.	601-021-00-3

- Flammable liquids, Cat. 2
- Toxic to reproduction, Cat. 2
- Aspiration hazard, Cat. 1

Safety Data Sheet

NUMIX WASH PRIMER

- Specific target organ toxicity (single exposure), Cat. 3
- Specific target organ toxicity (repeated exposure), Cat. 2
- Skin corrosion/irritation, Cat. 2

H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H361d	
H373	May cause damage to organs [organs] through prolonged or repeated exposure [route]

9. DI-N-BUTYL PHTHALATE

Concentration	5 10 % (weight)
EC no.	201-557-4
CAS no.	84-74-2
Index no.	607-318-00-4

- Toxic to reproduction, Cat. 1B
- Hazardous to the aquatic environment, short-term (acute), Cat. 1

H360Df	
H400	Very toxic to aquatic life

10. PHENOL , LIQUIFIED

Concentration	5 % (weight)
EC no.	203-632-7
CAS no.	108-95-2
Index no.	604-001-00-2

- Germ cell mutagenicity, Cat. 2
- Acute toxicity, inhalation, Cat. 3
- Acute toxicity, dermal, Cat. 3
- Acute toxicity, oral, Cat. 3
- Specific target organ toxicity (repeated exposure), Cat. 2
- Skin corrosion/irritation, Cat. 1B

H301	Toxic if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H331	Toxic if inhaled
H341	Suspected of causing genetic defects [route]
H373	May cause damage to organs [organs] through prolonged or repeated exposure [route]

Trade secret statement (OSHA 1910.1200(i))

For the wording of the listed hazard phrases refer to section 16

SECTION 4: First-aid measures

4.1 Description of necessary first-aid measures

General advice	Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
----------------	---

Safety Data Sheet

NUMIX WASH PRIMER

If inhaled	Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.
In case of skin contact	Immediately wash with water and soap and rinse thoroughly.
In case of eye contact	Rinse opened eye for several minutes under running water. Then consult a doctor.
If swallowed	If symptoms persist consult doctor.
Personal protective equipment for first-aid responders	No further relevant information available.

4.2 Most important symptoms/effects, acute and delayed

No further relevant information available.

4.3 Indication of immediate medical attention and special treatment needed, if necessary

No further relevant information available.

SECTION 5: Fire-fighting measures

5.1 Suitable extinguishing media

CO₂, sand, extinguishing powder. Do not use water.

5.2 Specific hazards arising from the chemical

No further relevant information available.

5.3 Special protective actions for fire-fighters

Wear mouth respiratory protective device.

Further information

No further relevant information available.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions

Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

6.3 Methods and materials for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents.

Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool location.
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.

Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

1. sec-Butyl acetate (CAS: 105-46-4)

PEL (Inhalation): 200 ppm (OSHA)
OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 950 mg/m³ (OSHA)
OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 200 ppm (Cal/OSHA)
OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): 200 ppm (NIOSH)
OSHA Annotated Table Z-1, www.osha.gov

2. sec-Butyl alcohol (CAS: 78-92-2)

PEL (Inhalation): 150 ppm (OSHA)
OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 450 mg/m³ (OSHA)
OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 100 ppm (Cal/OSHA)
OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): 100 ppm, (ST) 150 ppm (NIOSH)
OSHA Annotated Table Z-1, www.osha.gov

3. n-Butyl alcohol (CAS: 71-36-3)

PEL (Inhalation): 100 ppm (OSHA)
OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 300 mg/m³ (OSHA)
OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): (C) 50 ppm (Cal/OSHA)
OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): (C) 50 ppm (NIOSH)
OSHA Annotated Table Z-1, www.osha.gov

TLV® (Inhalation): 20 ppm (ACGIH)

4. XYLENES (MIXED) (CAS: 1330-20-7)

PEL (Inhalation): 100 ppm (OSHA)
OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 435 mg/m³ (OSHA)

Safety Data Sheet

NUMIX WASH PRIMER

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 100 ppm, (ST) 150 ppm, (C) 300 ppm (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): 100 ppm, (ST) 150 ppm (NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

5. 2-Butoxyethanol (CAS: 111-76-2 EC: 203-905-0)

PEL (Inhalation): 50 ppm (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 240 mg/m³ (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 20 ppm (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): 5 ppm (NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 20 ppm

97 mg/m³

California permissible exposure limits for chemical contaminants
(Title 8, Article 107)/Skin

TWA (Inhalation): 50 ppm

240 mg/m³; USA (OSHA)

USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air
Contaminants/Skin designation

The value in mg/m³ is approximate

TWA (Inhalation): 5 ppm

24 mg/m³; USA (NIOSH)

USA. NIOSH Recommended Exposure Limits/Potential for dermal absorption

TWA (Inhalation): 20 ppm; USA (ACGIH)

USA. ACGIH Threshold Limit Values (TLV)/Upper Respiratory Tract irritation Eye irritation Substances for which
there is a Biological Exposure Index or Indices (see BEI® section) Confirmed animal carcinogen with unknown
relevance to humans

TLV® (Inhalation): 20 ppm; USA (ACGIH)

OSHA Annotated Table Z-1, www.osha.gov

6. 1-Propanol (CAS: 71-23-8)

PEL (Inhalation): 200 ppm (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 500 mg/m³ (OSHA)

OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 200 ppm, (ST) 250 ppm (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): 200 ppm, (ST) 250 ppm (NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

7. Titanium(IV) oxide

PEL (Inhalation): 5 mg/m³ (Resp), 15 mg/m³ (Total) (OSHA)

Lower Respiratory Tract irritation

PEL (Inhalation): See PNOR (Cal/OSHA)

OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): Ca, (ultrafine particles), 2.4 mg/m³ (fine), 0.3 mg/m³(ultrafine), See Appendix A, See
Appendix C (NIOSH)

OSHA Annotated Table Z-1, www.osha.gov

Safety Data Sheet

NUMIX WASH PRIMER

TLV® (Inhalation): 10 mg/m³ (ACGIH)
OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 5 mg/m³ (Resp), 10 mg/m³ (Total) (Cal/OSHA)
OSHA Annotated Table Z-1, www.osha.gov

8. Toluene (CAS: 108-88-3)

PEL-TWA (Inhalation): 200 ppm (OSHA)

Central nervous system depression, causing fatigue, headache, confusion, paresthesia, dizziness, and muscular incoordination. Irritation of the eyes, mucous membranes, and upper respiratory tract

STEL (Inhalation): 150 ppm (OSHA)
OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): 100 ppm (375 mg/m³) (NIOSH)
Fatigue, weakness, confusion, headache, dizziness, drowsiness. Unconsciousness. Irritation of the eyes, respiratory tract, and skin

PEL-C (Inhalation): 300 ppm (OSHA)
OSHA Annotated Table Z-1, www.osha.gov

PEL-Peak (Inhalation): 500 ppm (10 minutes) (OSHA)
OSHA Annotated Table Z-1, www.osha.gov

TWA (Inhalation): 10 ppm (37 mg/m³) (Cal/OSHA)
Female reproductive toxicity, spontaneous abortion. Impaired color vision, impaired hearing, decreased performance in neurobehavioral analysis, changes in motor and sensory nerve conduction velocity, headache, and dizziness

TLV® (Inhalation): 20 ppm (75 mg/m³) (ACGIH)
Female reproductive system damage and pregnancy loss. Central nervous system impairment and visual impairment

STEL (Inhalation): 150 ppm (560 mg/m³) (NIOSH)
Fatigue, weakness, confusion, headache, dizziness, drowsiness. Unconsciousness. Irritation of the eyes, respiratory tract, and skin

PEL-C (Inhalation): 500 ppm Ceiling (Cal/OSHA)
Female reproductive toxicity, spontaneous abortion. Impaired color vision, impaired hearing, decreased performance in neurobehavioral analysis, changes in motor and sensory nerve conduction velocity, headache, and dizziness

PEL-ST (Inhalation): 150 ppm (560 mg/m³) - SKIN (Cal/OSHA)
Female reproductive toxicity, spontaneous abortion. Impaired color vision, impaired hearing, decreased performance in neurobehavioral analysis, changes in motor and sensory nerve conduction velocity, headache, and dizziness

9. DI-N-BUTYL PHTHALATE (CAS: 84-74-2)

PEL (Inhalation): 5 mg/m³ (OSHA)
OSHA Annotated Table Z-1, www.osha.gov

PEL (Inhalation): 5 mg/m³ (Cal/OSHA)
OSHA Annotated Table Z-1, www.osha.gov

REL (Inhalation): 5 mg/m³ (NIOSH)
OSHA Annotated Table Z-1, www.osha.gov

8.2 Appropriate engineering controls

No further relevant information available.

8.3 Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Wear tightly sealed goggles.

Wear protective face mask.

Safety Data Sheet

NUMIX WASH PRIMER

Skin protection

Wear protective gloves.

Body protection

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

Respiratory protection

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Thermal hazards

No further relevant information available.

Control banding approach

No further relevant information available.

Environmental exposure controls

No further relevant information available.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance/form (physical state, color, etc.)	Fluid
Odor	Characteristic
Odor threshold	Not determined.
pH	Not determined.
Melting point/freezing point	Undetermined.
Initial boiling point and boiling range	96.5 - 97.5 °C
Flash point	19 °C
Evaporation rate	Not determined.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability limits	Not determined.
Upper/lower explosive limits	Not determined.
Vapor pressure	25 hPa
Vapor density	Not determined.
Relative density	Not determined.
Solubility(ies)	Not miscible or difficult to mix with water.
Partition coefficient: n-octanol/water	Not determined.
Auto-ignition temperature	Product is not self-igniting.
Decomposition temperature	Not determined.
Viscosity	Not determined.
Explosive properties	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Oxidizing properties	Not determined.

Other safety information

No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity

No further relevant information available.

10.2 Chemical stability

Material is stable under normal conditions.

10.3 Possibility of hazardous reactions

No dangerous reactions known.

10.4 Conditions to avoid

No further relevant information available.

10.5 Incompatible materials

n-Butyl alcohol: Oxidizing agents, Alkali metals, Bases, Strong acids, Halogens

2-Butoxyethanol: Strong oxidizing agents

10.6 Hazardous decomposition products

2-Butoxyethanol: Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

No further relevant information available.

Skin corrosion/irritation

Irritant to skin and mucous membranes.

Serious eye damage/irritation

Strong irritant with the danger of severe eye injury.

Respiratory or skin sensitization

No sensitising effects known.

Germ cell mutagenicity

No further relevant information available.

Carcinogenicity

No further relevant information available.

Reproductive toxicity

No further relevant information available.

Summary of evaluation of the CMR properties

No further relevant information available.

Safety Data Sheet

NUMIX WASH PRIMER

STOT-single exposure

No further relevant information available.

STOT-repeated exposure

No further relevant information available.

Aspiration hazard

No further relevant information available.

Additional information

No further relevant information available.

SECTION 12: Ecological information

Toxicity

No further relevant information available.

Persistence and degradability

No further relevant information available.

Bioaccumulative potential

No further relevant information available.

Mobility in soil

No further relevant information available.

Results of PBT and vPvB assessment

Not applicable.

Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations

Disposal of the product

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal of contaminated packaging

Disposal must be made according to official regulations.

Waste treatment

Disposal must be made according to official regulations.

Sewage disposal

Disposal must be made according to official regulations.

Other disposal recommendations

No further relevant information available.

SECTION 14: Transport information

DOT (US)

UN Number: UN 1263

Class: 3 Flammable liquids.

Packing Group: II

Proper Shipping Name: UN 1263 PAINT

Reportable quantity (RQ): 5L

Safety Data Sheet

NUMIX WASH PRIMER

IMDG

UN Number: UN 1263
Class: 3 Flammable liquids.
Packing Group: II
EMS Number: F-E,S-D
Proper Shipping Name: UN 1263 PAINT

IATA

UN Number: UN 1263
Class: 3 Flammable liquids.
Packing Group: II
Proper Shipping Name: UN 1263 PAINT

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

Massachusetts Right To Know Components

Chemical name: sec-Butyl acetate
CAS number: 105-46-4

New Jersey Right To Know Components

Common name: sec-BUTYL ACETATE
CAS number: 105-46-4

Pennsylvania Right To Know Components

Chemical name: Acetic acid, 1-methylpropyl ester
CAS number: 105-46-4

Massachusetts Right To Know Components

Chemical name: sec-Butyl alcohol
CAS number: 78-92-2

New Jersey Right To Know Components

Common name: sec-BUTYL ALCOHOL
CAS number: 78-92-2

Pennsylvania Right To Know Components

Chemical name: 2-Butanol
CAS number: 78-92-2

Massachusetts Right To Know Components

Chemical name: n-Butyl alcohol
CAS number: 71-36-3

New Jersey Right To Know Components

Common name: n-BUTYL ALCOHOL
CAS number: 71-36-3

Pennsylvania Right To Know Components

Chemical name: 1-Butanol
CAS number: 71-36-3

Safety Data Sheet

NUMIX WASH PRIMER

Massachusetts Right To Know Components

Chemical name: Xylene (mixed isomers)
CAS number: 1330-20-7

New Jersey Right To Know Components

Common name: XYLENES
CAS number: 1330-20-7

Pennsylvania Right To Know Components

Chemical name: Benzene, dimethyl-
CAS number: 1330-20-7

Massachusetts Right To Know Components

Ethylene glycol monobutyl ether
CAS: 111-76-2

New Jersey Right To Know Components

Ethylene glycol monobutyl ether
CAS: 111-76-2

Pennsylvania Right To Know Components

Ethylene glycol monobutyl ether
CAS: 111-76-2

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:
Ethylene glycol monobutyl ether
CAS: 111-76-2

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

New Jersey Right To Know Components

Common name: PROPYL ALCOHOL
CAS number: 71-23-8

Pennsylvania Right To Know Components

Chemical name: 1-Propanol
CAS number: 71-23-8

California Prop. 65 Components

Titanium dioxide (airborne, unbound particles of respirable size)

WARNING! This product contains a chemical known to the State of California to cause cancer.

Safety Data Sheet

NUMIX WASH PRIMER

Titanium dioxide
CAS-No. 13463-67-7

New Jersey Right To Know Components

Chemical name: Titanium dioxide
CAS number: 13463-67-7

Pennsylvania Right To Know Components

Chemical name: Titanium dioxide
CAS number: 13463-67-7

Massachusetts Right To Know Components

Chemical name: Toluene
CAS number: 108-88-3

New Jersey Right To Know Components

Chemical name: Toluene
CAS number: 108-88-3

California Prop. 65 Components

State of California to cause birth defects or other reproductive harm.
Toluene
CAS-No. 108-88-3

Pennsylvania Right To Know Components

Chemical name: Toluene
CAS number: 108-88-3

California Prop. 65 components

Chemical name: Toluene
CAS number: 108-88-3
01/01/1991 - Developmental toxicity
07/08/2009 - Female reproductive toxicity (de-listed 07/03/2014)

Massachusetts Right To Know Components

Chemical name: Dibutyl phthalate
CAS number: 84-74-2

New Jersey Right To Know Components

Common name: DI-n-BUTYL PHTHALATE
CAS number: 84-74-2

Pennsylvania Right To Know Components

Chemical name: 1,2-Benzenedicarboxylic acid, dibutyl ester
CAS number: 84-74-2

California Prop. 65 components

Chemical name: DI-N-BUTYL PHTHALATE
CAS number: 84-74-2
02/12/2005 - Developmental toxicity
02/12/2005 - Female reproductive toxicity
02/12/2005 - Male reproductive toxicity

Safety Data Sheet

NUMIX WASH PRIMER

Massachusetts Right To Know Components

Chemical name: Phenol

CAS number: 108-95-2

New Jersey Right To Know Components

Common name: PHENOL

CAS number: 108-95-2

Pennsylvania Right To Know Components

Chemical name: Phenol

CAS number: 108-95-2

15.2 Chemical Safety Assessment

No further relevant information available.

SECTION 16: Other information

16.1 Further information/disclaimer

DISCLAIMER: The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of information for their particular purposes. In no event shall National Paints Factories Co. Ltd be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, whatsoever arising, even if National Paints Factories Co. Ltd has been advised of the possibility of such damages.