

TECHNICAL DATA SHEET

NUMIX 1K READY-MIX COLORS

PRODUCT DESCRIPTION

Numix 1K Ready-Mix Colors is a one-component, ready-mix, fast-moving color system based on OEM standards.

FEATURES

- All colors meet OEM standards.
- Excellent coverage.
- Smooth finish.
- Easy application.

SUITABLE SUBSTRATES

Numix 1K Ready-Mix Colors is suitable to apply over 1K and 2K Numix Acrylic Primer, old/original paint work, and all existing OEM finishes.

TECHNICAL NOTES:

	It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.
	Use Numix Degreaser to remove grease, oil and other contaminants. Use clean quality tack rags or wiping towels, one for wetting and one for drying with wipe on wipe off.
	Stir the Numix 1K Ready-Mix Colors properly before use.
	The choice of thinner should be made according to application temperature and size of repair. For mixing use Numix mixing ruler.
	Always use filter paper to avoid the risk of dust particles.
	Clean the gun properly after usage with cleaning thinner.
	The VOC content of this product in ready to use form is 600- 700 g/l of VOC

TECHNICAL DATA SHEET

APPLICATION DETAILS: (Numix 1K Ready-Mix Colors)

	Mixing Ratio	Product		Mix By Volume		
		Numix 1K Ready-Mix Colors		100		
		Thinner		100		
	Pot life at 20°C		N/A			
	Spray viscosity at 20°C		FORD 4		17 - 20s	
	Spray equipment	Type of Gun		Nozzle Size	Distance	Pressure
		Gravity Feed/Suction feed		1.3-1.4 mm	15-20 cm	2-3 bar
		HVLP		1.3-1.4 mm	15-20 cm	1.5 bar
	Number of coats	2 - 3 Coats				
	Flash time	3 - 5 min between coats				
	DFT	15 - 20 microns. depends on no. of coats.				
	Drying time @ 20°C	Surface Dry				
		25 mins.				

REMARKS

- Store the paint in proper storage conditions as per the local regulations.
- Keep the paint container in a sealed condition under a shed, away from direct sunlight and extreme temperatures.
- Do not keep paint material near any ignition sources. Do not put back the half or unused material back in the original container, containing the supplied paint to avoid contamination.
- Handle with care. Stir well before use. 48 months @ 30°C, in original sealed container, with proper storage conditions.

NOTE: We warranty the quality of our product and this data sheet represents test results and practical experience obtained under controlled conditions. We reserve the right to change data without prior notice.