

TECHNICAL DATA SHEET

NUMIX ACCELERATOR

PRODUCT DESCRIPTION

Numix Accelerator is an easy-to-use additive that helps clear coats and topcoats dry and harden much faster than usual. By speeding up the chemical process that makes the coating cure, it allows you to handle, polish, or move finished parts sooner.

FEATURES

- Faster drying time
- Great for small repairs
- Improves efficiency
- Easy to use

RECOMMENDED USES

Suitable for curing at temperatures between 15-25°C, designed for spot and panel repairs.

TYPICAL PROPERTIES

Color Dry Film	Transparent Clear
Finish Dry Film	Glossy
Specific Gravity	0.92 ± 0.02 g/ml
Volume Solids	10 ± 2 %
Viscosity	13 - 15 sec

APPLICATION

Add just 1–3% of Numix Accelerator to your 2K topcoats mix, and it can cut drying time by up to half. If you're using heat, it can reduce baking time to as little as 10–15 minutes—helping you finish jobs much faster.

REMARKS

- Store the paint in proper storage conditions as per the local regulations.
- Keep the paint container in a sealed condition under a shed, away from direct sunlight and extreme temperatures.
- Do not keep paint material near any ignition sources. Do not put back the half or unused material back in the original container, containing the supplied paint to avoid contamination.
- Handle with care. Stir well before use. 24 months @ 30°C, in original sealed container, with proper storage conditions.

NOTE: We warranty the quality of our product and this data sheet represents test results and practical experience obtained under controlled conditions. We reserve the right to change data without prior notice.