

TECHNICAL DATA SHEET

NUMIX ANTI-SILICONE

PRODUCT DESCRIPTION

Numix Anti-Silicone is an additive specially designed for 2K polyurethane top coats. It can improve levelling and remove paint film defects such as fish eyes or craters.

FEATURES

- Improves levelling.
- Removes fish eyes

ADVANTAGES

- Leveling improvement of car refinish coating caused by contamination like oil, greases and silicones.

APPLICATION

	Mixing ratio	Add 2 - 3 ml by weight or 1% by volume to a ready to spray paint (Clear Coats, and Topcoats).
---	---------------------	---

- Use only if a defect occurs in the 1st coat, the systematic use of anti-cratering additive will supersaturate the environment and create other surface defects.
- Not recommended for undercoats or basecoats.

REMARKS

- Store the paint in proper storage conditions as per the local regulations.
- Keep the paint container in a sealed condition under a shed, away from direct sunlight and extreme temperatures.
- Do not keep paint material near any ignition sources. Do not put back the half or unused material back in the original container, containing the supplied paint to avoid contamination.
- Handle with care. Stir well before use. 48 months @ 30°C, in original sealed container, with proper storage conditions.

NOTE: We warranty the quality of our product and this data sheet represents test results and practical experience obtained under controlled conditions. We reserve the right to change data without prior notice.