

TECHNICAL DATA SHEET

NUMIX DEGREASER


PRODUCT DESCRIPTION

Numix Degreaser is a solvent specially selected to remove grease, oil and other contaminants from bare metal, aluminum, galvanized steel, existing finishes; polyester putty, primer surfacer and plastic substrate.

FEATURES

- General-purpose cleaner.
- Easy surface treatment to any substrate, bare or existing refinishes.

TECHNICAL NOTES:

	It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.
	Use tight-fitting, disposable nitrile gloves.
	The VOC content of this product in ready to use form is 185 g/l of VOC.

APPLICATION

1. Wash the vehicles with soap and warm water to remove water soluble contaminants.
2. Wash down the repaired area with Numix Degreaser to remove any other contaminants.
3. With a clean towel dry off the Degreaser before evaporation to ensure contaminants removal.

PRECAUTION

Never allow for the cleaned vehicles to be touched with bare hands, moisture and oils which may cause adhesion or blistering problems

REMARKS

- Store the paint in proper storage conditions as per the local regulations.
- Keep the paint container in a sealed condition under a shed, away from direct sunlight and extreme temperatures.
- Do not keep paint material near any ignition sources. Do not put back the half or unused material back in the original container, containing the supplied paint to avoid contamination.
- Handle with care. Stir well before use. 48 months @ 30°C, in original sealed container, with proper storage conditions.

NOTE: We warranty the quality of our product and this data sheet represents test results and practical experience obtained under controlled conditions. We reserve the right to change data without prior notice.