

TECHNICAL DATA SHEET

NUMIX GUMA VINYL GUARD (S.B)

PRODUCT DESCRIPTION

Numix Guma Vinyl Guard is a special resin blend base undercoat which gives a tough textured undercoat to the refinishing, giving extra protection against stone and gravel chipping. It has good color retention, high resistance to severe weather conditions, good durability and flexibility.

FEATURES

- Coarse texture.
- High coverage.
- Corrosion and abrasion resistance.

RECOMMENDED USES

For refinishing plastisol area on cars as replacement coating.

TECHNICAL NOTES:

	It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.
	Use Numix Degreaser to remove grease, oil and other contaminants. Use clean quality tack rags or wiping towels, one for wetting and one for drying with wipe on wipe off.
	Shake the Numix Guma Vinyl Guard properly before use.
	Clean the gun properly after usage with cleaning thinner.
	The VOC content of this product in ready to use form is 508 g/l of VOC.

TECHNICAL DATA SHEET

APPLICATION DETAILS: (Numix Guma Vinyl Guard)

- Remove all rust scale oil and grease from surfaces to be coated.
- The surface must be clean and dry.
- Can be applied to bare or primed metal.
- If applied to composite plastic as a sound deadening material; apply first Numix Plastic Primer prior to applying undercoat this will increase adhesion.

	Mixing Ratio	Ready to spray.	
	Mixing	Dilute with lacquer thinner if required to reach the desired flow and spray viscosity.	
	Number of coats	2 coats.	
	Spray Equipment	Undercoat Spray Gun.	
		Distance	Pressure
		15 - 20 cm	3 - 4 bar
	Flash Time	3 - 5 minutes.	
	Drying time @ 20°C	Hard Dry 10 - 30 mins.	
	DFT	100 microns.	

REMARKS

- Store the paint in proper storage conditions as per the local regulations.
- Keep the paint container in a sealed condition under a shed, away from direct sunlight and extreme temperatures.
- Do not keep paint material near any ignition sources. Do not put back the half or unused material back in the original container, containing the supplied paint to avoid contamination.
- Handle with care. Stir well before use. 18 months @ 30°C, in original sealed container, with proper storage conditions.

NOTE: We warranty the quality of our product and this data sheet represents test results and practical experience obtained under controlled conditions. We reserve the right to change data without prior notice.