

TECHNICAL DATA SHEET

NUMIX PLASTICIZER 401

PRODUCT DESCRIPTION

Numix Plasticizer is designed to increase flexibility, impact resistance, chip resistance, and UV protection in Numix 2K products. It mixes easily and does not affect drying or curing time.

FEATURES

- Improves flexibility of the Numix 2K products

SUITABLE SUBSTRATES

To improve the flexibility of Numix 2K Primer, Numix 2K Top Coat, Numix Clear Coat and over a wide variety of semi-rigid and flexible plastic parts.

TECHNICAL NOTES:

	It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.
	Stir the Numix Plasticizer properly before use.
	Always use filter paper to avoid the risk of dust particles.
	Clean the gun properly after usage with cleaning thinner.
	The VOC content of this product in ready to use form is 627 g/l of VOC.

APPLICATION DETAILS: (Numix Plasticizer 401)

	Mixing ratio	Add 5 -10% to a liter of paint mixture (with Hardener and Thinner). Mix well before application.
---	---------------------	--

REMARKS

- Store the paint in proper storage conditions as per the local regulations.
- Keep the paint container in a sealed condition under a shed, away from direct sunlight and extreme temperatures.
- Do not keep paint material near any ignition sources. Do not put back the half or unused material back in the original container, containing the supplied paint to avoid contamination.
- Handle with care. Stir well before use. 48 months @ 30°C, in original sealed container, with proper storage conditions.

NOTE: We warranty the quality of our product and this data sheet represents test results and practical experience obtained under controlled conditions. We reserve the right to change data without prior notice.