

TECHNICAL DATA SHEET

NUMIX RETARDER

PRODUCT DESCRIPTION

A thinner of special composition which can be added with various thinners at high temperatures and/or when large vehicles are to be painted, to keep 1K/2K product film dry slower to avoid overspray for a better smooth finish, certainly at high temperature. It will not affect the gloss level.

FEATURES

- Excellent performance at high temperatures.
- Slow evaporating rate.

RECOMMENDED USES

At high temperatures (above 40°C) and when large vehicles are to be painted.

APPLICATION DETAILS: (Numix Retarder)

	Mixing Ratio	At high temperatures (above 40°C) and when large vehicles are to be painted, it is recommended to add 10 - 30 % by volume of Numix Retarder Thinner to the thinner specified for the product concerned at higher temperatures (204 Thinner Slow or 206 Extra Slow, for example). Next add this mixture to the product, using the mixing ratio specified in its technical data sheet. At temperatures above 40°C, Numix Retardant Thinner can also be used pure. In this case, add Numix Retarder Thinner to the product as specified in its technical data sheet, using it as a substitute for the thinner originally recommended
---	---------------------	---

REMARKS

- Store the paint in proper storage conditions as per the local regulations.
- Keep the paint container in a sealed condition under a shed, away from direct sunlight and extreme temperatures.
- Do not keep paint material near any ignition sources. Do not put back the half or unused material back in the original container, containing the supplied paint to avoid contamination.
- Handle with care. Stir well before use. 48 months @ 30°C, in original sealed container, with proper storage conditions.

NOTE: We warranty the quality of our product and this data sheet represents test results and practical experience obtained under controlled conditions. We reserve the right to change data without prior notice.