

TECHNICAL DATA SHEET

NUMIX SPOT PUTTY DARK BEIGE

PRODUCT DESCRIPTION

Numix Spot Putty Dark Beige is a fine-textured knifing 1K filler for minor surface imperfections, scratches and pinholes on cars and commercial vehicle bodies. Recommended for professional car repair and refinishing. Excellent wet and dry sanding properties.

FEATURES

- Easily identifies the smallest scratches.
- Easy sanding, leaving a smooth finish.
- Fast drying.
- Can be sanded or recoated quickly

SUITABLE SUBSTRATES

Numix Spot Putty Dark Beige is suitable for filling minor surface flaws and scratch marks on the car and commercial vehicle bodies. Applied over a fully-cured 2K Primer or Epoxy Primer surfacer, sanded and cleaned.

TECHNICAL NOTES:

	It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.
	Use tight-fitting, disposable nitrile gloves.
	Use Numix Degreaser to remove grease, oil and other contaminants. Use clean quality tack rags or wiping towels, one for wetting and one for drying with wipe on wipe off.
	Stir the Numix Spot Putty Dark Beige properly before use.
	The VOC content of this product in ready to use form is 558 g/l of VOC.

TECHNICAL DATA SHEET

APPLICATION DETAILS: (Numix Spot Putty Dark Beige)

	Mixing ratio	Ready to use	
	Application	Apply by knife. 1 - 2 thin coats. Allow 5- 10 minutes between coats.	
	Pot life at 20°C	N/A	
	DFT	Depends No. of coats.	
	Drying time @ 20°C	Surface Dry	Dry to Sand
		15 min.	20 min.
	Dry Sanding	P400, P500 (we recommend using a black dry guide coat for better results and uniformly sanding).	
	Wet Sanding	P800 – P1000 to get a smooth surface.	

REMARKS

- Store the paint in proper storage conditions as per the local regulations.
- Keep the paint container in a sealed condition under a shed, away from direct sunlight and extreme temperatures.
- Do not keep paint material near any ignition sources. Do not put back the half or unused material back in the original container, containing the supplied paint to avoid contamination.
- Handle with care. Stir well before use. 18 months @ 30°C, in original sealed container, with proper storage conditions.

NOTE: We warranty the quality of our product and this data sheet represents test results and practical experience obtained under controlled conditions. We reserve the right to change data without prior notice.